

# **SAFETY DATA SHEET**

# Nilbac Dry touch sanitiser Max blast

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name Nilbac Dry touch sanitiser Max blast

Product number NDT750

Internal identification DH746

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Air freshener Room purifier

Uses advised against
Use only for intended applications.

# 1.3. Details of the supplier of the safety data sheet

Supplier James Briggs Ltd

Salmon Fields

Royton Oldham OL2 6HZ 0161 627 0101

sds@jamesbriggs.co.uk

# 1.4. Emergency telephone number

# SECTION 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Not Classified

Environmental hazards Not Classified

# 2.2. Label elements

# Hazard pictograms



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

# Nilbac Dry touch sanitiser Max blast

**Precautionary statements** P102 Keep out of reach of children.

P261 Avoid breathing vapour/ spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/ attention.

**Detergent labelling** ≥ 30% aliphatic hydrocarbons, < 5% cationic surfactants, < 5% perfumes, Contains

LINALOOL

Supplementary precautionary

statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

# 2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

# SECTION 3: Composition/information on ingredients

## 3.2. Mixtures

Petroleum gases, liquefied		60-100%
CAS number: 68476-85-7	EC number: 270-704-2	
Classification Flam. Gas 1 - H220 Press. Gas (Liq.) - H280		

Ethanol		10-30%
CAS number: 64-17-5	EC number: 200-578-6	REACH registration number: 01-
		2119457610-43-XXXX

# Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319

STOT SE 3 - H336

1-5%
-7 REACH registration number: 01- 2119457558-25-XXXX
1

Propane-1,2-diol			<1%
CAS number: 57-55-6	EC number: 200-338-0	REACH registration number: 01-2119456809-23-XXXX	
Classification Not Classified			

# Nilbac Dry touch sanitiser Max blast

Diethyl phthalate <1%

CAS number: 84-66-2 EC number: 201-550-6

Classification
Not Classified

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

# SECTION 4: First aid measures

# 4.1. Description of first aid measures

General information If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical

personnel.

**Inhalation** Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist. Place unconscious person on their side in the recovery position and

ensure breathing can take place.

**Ingestion** Rinse mouth thoroughly with water. If in doubt, get medical attention promptly. Due to the

small packaging, the risk of ingestion is minimal. Do not induce vomiting unless under the

direction of medical personnel.

Skin contact Remove contamination with soap and water or recognised skin cleansing agent.

Eye contact Remove any contact lenses and open eyelids wide apart. Rinse with water. Get medical

attention if any discomfort continues.

**Protection of first aiders**First aid personnel should wear appropriate protective equipment during any rescue.

#### 4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

**Inhalation** Spray/mists may cause respiratory tract irritation.

**Ingestion** Due to the physical nature of this product, it is unlikely that ingestion will occur.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact Vapour or spray in the eyes may cause irritation and smarting. Particles in the eyes may

cause irritation and smarting.

# 4.3. Indication of any immediate medical attention and special treatment needed

**Specific treatments** Treat symptomatically.

## SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder

or water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

## 5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and

propellant. Vapours may form explosive mixtures with air.

# Nilbac Dry touch sanitiser Max blast

# Hazardous combustion products

Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Carbon monoxide (CO). Carbon dioxide (CO2).

# 5.3. Advice for firefighters

# Protective actions during firefighting

Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

# Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

# SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

#### Personal precautions

Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

#### **Environmental precautions**

Avoid discharge into drains or watercourses or onto the ground. Not considered to be a significant hazard due to the small quantities used.

# 6.3. Methods and material for containment and cleaning up

# Methods for cleaning up

Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Provide adequate ventilation. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

## 6.4. Reference to other sections

# Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

# SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

## Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. The product is flammable. Avoid exposing aerosol containers to high temperatures or direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Do not expose to temperatures exceeding 50°C/122°F. Avoid inhalation of vapours and spray/mists. Avoid contact with eyes.

# Nilbac Dry touch sanitiser Max blast

Advice on general occupational hygiene

Good personal hygiene procedures should be implemented. Wash contaminated skin thoroughly after handling. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash after use and before eating, smoking and

using the toilet.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). Keep away from oxidising materials,

heat and flames. Store in a cool and well-ventilated place. Protect from sunlight. Keep containers upright. Protect containers from damage. Do not expose to temperatures

exceeding 50°C/122°F. Do not store near heat sources or expose to high temperatures. Store

in accordance with national regulations.

Storage class Chemical storage. Aerosol containers and lighters

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

## Occupational exposure limits

#### Petroleum gases, liquefied

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

#### Ethanol

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m<sup>3</sup>

# Propan-2-ol

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m<sup>3</sup>

# Propane-1,2-diol

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate

Long-term exposure limit (8-hour TWA): WEL 150 ppm 474 mg/m³ total vapour and particulates

# Diethyl phthalate

Long-term exposure limit (8-hour TWA): WEL 5 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 10 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit.

# Ethanol (CAS: 64-17-5)

**DNEL** Workers - Inhalation; Long term systemic effects: 950 mg/m³

Workers - Inhalation; Long term local effects: 1900 mg/m<sup>3</sup> Workers - Dermal; Long term systemic effects: 343 mg/kg/day

General population - Inhalation; Long term systemic effects: 114 mg/m³ General population - Inhalation; Long term local effects: 950 mg/m³ General population - Dermal; Long term systemic effects: 206 mg/kg/day General population - Oral; Long term systemic effects: 87 mg/kg/day

# Nilbac Dry touch sanitiser Max blast

PNEC - Fresh water; 0.96 mg/l

- marine water; 0.79 mg/l

- STP; 580 mg/l

Sediment (Freshwater); 3.6 mg/kgSediment (Marinewater); 2.9 mg/kg

Soil; 0.63 mg/kgOral; 380 mg/kg

# Propan-2-ol (CAS: 67-63-0)

**DNEL** Workers - Inhalation; Long term systemic effects: 500 mg/m³

Workers - Dermal; Long term systemic effects: 888 mg/kg/day

General population - Inhalation; Long term systemic effects: 89 mg/m³ General population - Dermal; Long term systemic effects: 319 mg/kg/day General population - Oral; Long term systemic effects: 26 mg/kg/day

PNEC - Fresh water; 140.9 mg/l

- marine water; 140.9 mg/l

- STP; 2251 mg/l

Sediment (Freshwater); 552 mg/kgSediment (Marinewater); 552 mg/kg

Soil; 28 mg/kgOral; 160 mg/kg

# Propane-1,2-diol (CAS: 57-55-6)

**DNEL** Workers - Inhalation; Long term systemic effects: 168 mg/m³

Workers - Inhalation; Long term local effects: 10 mg/m3

General population - Inhalation; Long term systemic effects: 50 mg/m³ General population - Inhalation; Long term local effects: 10 mg/m³

PNEC - Fresh water; 260 mg/l

- marine water; 26 mg/l - STP; 20000 mg/l

Sediment (Freshwater); 572 mg/kgSediment (Marinewater); 57.2 mg/kg

- Soil; 50 mg/kg

## 8.2. Exposure controls

Appropriate engineering

Provide adequate ventilation. Observe any occupational exposure limits for the product or

ingredients.

**Hand protection** No specific hand protection recommended.

Other skin and body

protection

controls

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke

when using this product.

# SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Colourless.

Odour Perfume. Fresh Linen

# Nilbac Dry touch sanitiser Max blast

Initial boiling point and range -40 - -2°C (LPG)

Flash point -104°C (LPG)

Upper/lower flammability or

explosive limits

1.4 - 10.9%(V)(LPG)

Auto-ignition temperature 365 °C / 689 °F (LPG)

9.2. Other information

# SECTION 10: Stability and reactivity

## 10.1. Reactivity

**Reactivity** See the other subsections of this section for further details.

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

The following materials may react strongly with the product: Oxidising agents.

#### 10.4. Conditions to avoid

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised

container: may burst if heated Avoid heat, flames and other sources of ignition. Avoid the

following conditions: Freezing.

# 10.5. Incompatible materials

Materials to avoid No specific requirements are anticipated under normal conditions of use.

#### 10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

# SECTION 11: Toxicological information

# 11.1. Information on toxicological effects

Inhalation Gas or vapour may irritate the respiratory system. May cause nausea, headache, dizziness

and intoxication. Vapour may irritate respiratory system/lungs.

**Ingestion** Due to the physical nature of this product, it is unlikely that ingestion will occur. Ingestion may

cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. May cause chemical burns in mouth, oesophagus and stomach. May cause discomfort if swallowed. May

cause stomach pain or vomiting.

**Skin contact** Repeated exposure may cause skin dryness or cracking.

**Eye contact** May cause eye irritation. May cause serious eye damage.

Route of exposure Inhalation Ingestion Skin and/or eye contact

# SECTION 12: Ecological information

# 12.1. Toxicity

**Toxicity** The product is not believed to present a hazard due to its physical nature.

## 12.2. Persistence and degradability

# Nilbac Dry touch sanitiser Max blast

Persistence and degradability The degradability of the product is not known.

# 12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

**Mobility** No data available.

## 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

## 12.6. Other adverse effects

Other adverse effects None known.

## SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. This material and

its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Dispose of waste product or used

containers in accordance with local regulations

**Disposal methods**Do not empty into drains. Empty containers must not be punctured or incinerated because of

the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with

the requirements of the local Waste Disposal Authority.

Waste class

The waste code classification is to be carried out according to the European Waste Catalogue

(EWC).

# **SECTION 14: Transport information**

# 14.1. UN number

**UN No. (ADR/RID)** 1950

**UN No. (IMDG)** 1950

**UN No. (ICAO)** 1950

**UN No. (ADN)** 1950

# 14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

**AEROSOLS** 

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

## 14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

# Nilbac Dry touch sanitiser Max blast

ICAO class/division 2.1

ADN class 2.1

## Transport labels



## 14.4. Packing group

ADR/RID packing group None

IMDG packing group None

ICAO packing group None

ADN packing group None

# 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

# 14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

# 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

# SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EH40/2005 Workplace exposure limits.

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Council Directive of 20 May 1975 on the approximation of the laws of the Member States

relating to aerosol dispensers (75/324/EEC) (as amended).

# 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

# Inventories

# Nilbac Dry touch sanitiser Max blast

#### **EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

# SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

IATA: International Air Transport Association.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate.

LC<sub>50</sub>: Lethal Concentration to 50 % of a test population.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

EC50: 50% of maximal Effective Concentration.

PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations

and acronyms

Aerosol = Aerosol

Key literature references and

sources for data

Source: European Chemicals Agency, http://echa.europa.eu/

Classification procedures according to Regulation (EC)

1272/2008

Aerosol 1 - H222, H229: : Expert judgement.

Revision date 22/05/2020

Revision 2

Supersedes date 14/05/2020

SDS number 6536

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.