Pharmacy Essential Refrigerator

47L Pharmacy Essential Countertop Fridge with Solid Door

Product code PESR47DC-UK

SKU code 444411286







Key features

- √ Temperature range of +2°C to +8°C
- √ Air temperature probe





Temperatures are easy to read on the clear digital display. Read, record, and reset simply with the touch of a button.



Fitted Lock

Integrated lock, comes with two keys for added security and access control, to keep contents safe.

- ✓ Audible and visual temperature alarms
- √ Solid and glass door options



Flexible Storage

Multiple shelf positions provide a flexible storage options for all your needs.



Anti-Microbial Handle

Our handles have an anti-microbial powder coating which inhibits the growth of microbes to help prevent cross contamination.



Product Information

Brand	Lec Medical
	Pharmacy
Sub-Brand	e .: .:
SKU Code	
EAN Code	
GDMA Code	DESC / ED S
Description	Countertop

Door Specification

Painted Steel / HIPS*
Solid
Hinged, Reversible
Flat
n/a
n/a
905mm
Yes

Product Features

Gross Capacity (litres)	47L
Net Capacity (litres)	35L
Temperature Range	+2°C to +8°C
Open Door Sensor	Yes
Key Lock	Yes, 2 Keys
Digital Lock	No
Porthole	Yes
Porthole Size (Ø Diameter)	16mm
Porthole Location	Rear Bottom (Right)
Controller Type	Digital DC, External
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms	Yes
Interior Light	No
Light Type	n/a
Light Activation	n/a
Fan - Type	Yes - Axial
Spark Free	No
Defrost setting	Auto (Off Cycle)
Battery Back Up/Hours	No
Bluetooth	No
NFC	No
WIFI	No
GSM-4G	No
Number of Probes	1
Probe Type	Air
Anti Microbial Handle	Yes

Technical Information

Noise Level (dB)	46.7dB
Colour	White/Green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Ambient Temperature Range	16°C to 32°C
Refrigerant Type / Weight (g)	R600a/25g
CFC Free	Yes
HFC Free	Yes
HCFC Free	Yes
Ammonia Free	Yes
Insulation Thickness (mm)	35mm
Insulation Type	High Density Polyurothane Foam
Blowing Agent	Cyclopentane
Certification	CE/UKCA
ATEX Zone Classification	n/a

Internal Specification

Number of Shelves	1
Number of Shelf Positions	3
	418mm x 200mm x 6mm
	n/a
	White Polythene Coated Wire
	n/a
	n/a
	n/a
Drawer Size 2 (mm) (WxDxH)	n/a
Drawer Material	n/a
Number of Baskets	1
Basket Material	White Polythene Coated Wire
Basket Size (mm) (WxDxH)	396mm x 165mm x 150mm

Power/Installation

UK 3 Pin Plug Power Cord	Yes
EU Schuko 2 pin plug Power Cord	Yes
	No
Voltage Supply (V)	220-240V
Frequency (Hz)	
Max Power (W)	70W
Max Current Rating (A)	0.6A
Energy Consumption (kWh/24h)	0.54kWh/24h
Energy Consumption AE (kWh)	197.1kWh
Heat Output Estimated at 22°C (kJ)	1944kJ
Adjustable Feet (Number & position)	2 adjustable (front)

Weights & Dimensions

4/5/11/1
445mm
565mm
505mm
405mm x 355mm x 425mm
18.32kg
505mm
510mm
585mm
20.4kg
China

