Pharmacy Plus Bluetooth

Enabled Refrigerator

158L Pharmacy Plus Undercounter Fridge with Glass Door

Product code PPGR158BT-UK

SKU code 444411309







Key features

- √ Temperature range of +2°C to +8°C
- √ Audible and visual temperature alarms
- √ Solid and glass door options
- ✓ Integrated lock, supplied with 2 keys for added security











Bluetooth Connected Controller

Our controller is Bluetooth enabled and allows for simple, contactless monitoring of temperature and alarm history, via the official Lec Medical app. Battery back-up, provides continuous temperature monitoring in the event of power outage.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.

Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



Product Information

| Brand | Lec Medical |
|-------------|---------------|
| | Pharmacy |
| Sub-Brand | Pharmacy Plus |
| SKU Code | 444411309 |
| EAN Code | |
| GDMA Code | DDODIEGDT |
| Description | Under Counter |

Door Specification

| Door Finish | PVC / Glass |
|-------------------------------|--------------------|
| Door Type | Glass |
| Door Style | Hinged, Reversible |
| Door Liner | -1 |
| Number of Door Trays | n/a |
| Number of Door Tray Positions | |
| Door Open Depth (mm) | 1150mm |
| Replacement Door Seal | Yes |

Product Features

| Gross Capacity (litres) | 158L |
|------------------------------|----------------------|
| Net Capacity (litres) | 154L |
| Temperature Range | +2°C to +8°C |
| Open Door Sensor | Yes |
| Key Lock | Yes, 2 Keys |
| Digital Lock | No |
| Porthole | Yes |
| Porthole Size (Ø Diameter) | 16mm |
| Porthole Location | Rear Bottom (Right) |
| Controller Type | Digital BT, External |
| Temperature Display on Panel | Yes |
| Temperature Alarm | Yes |
| Remote Alarm Contacts | Yes |
| Audible Alarms | Yes |
| Visual Alarms | Yes |
| Interior Light | Yes |
| Light Type | LED |
| Light Activation | Door Switch / App |
| Fan - Type | Yes - Tangential |
| Spark Free | No |
| Defrost setting | Auto (Off Cycle) |
| Battery Back Up/Hours | Yes/48hrs |
| Bluetooth | Yes |
| NFC | Yes |
| WIFI | No |
| GSM-4G | No |
| Number of Probes | 2 |
| Probe Type | Air & Load |
| Anti Microbial Handle | Yes |
| | |

Technical Information

| <u>recinited i</u> | |
|-------------------------------|--------------------------------|
| Noise Level (dB) | 40.1dB |
| Colour | White/green |
| External Finish | Painted Steel |
| Internal Finish | HIPS* |
| Type of plastic | SRL800 (HIPS/ABS mix) |
| Ambient Temperature Range | 16°C to 32°C |
| Refrigerant Type / Weight (g) | R600a/28g |
| CFC Free | Yes |
| HFC Free | Yes |
| HCFC Free | Yes |
| Ammonia Free | Yes |
| Insulation Thickness (mm) | 45mm |
| Insulation Type | High Density Polyurethane Foam |
| Blowing Agent | Cyclopentane |
| Certification | CE/UKCA |
| ATEX Zone Classification | n/a |

Internal Specification

| Number of Shelves | 4 |
|----------------------------|-----------------------------|
| Number of Shelf Positions | 5 |
| Shelf Size 1 (mm) (WxDxH) | 496mm x 405mm x 6mm |
| Shelf Size 2 (mm) (WxDxH) | 493mm x 265mm x 6mm |
| Shelf Material | White Polythene Coated Wire |
| Number of Drawers | n/a |
| Number of Drawer Positions | n/a |
| Drawer Size 1 (mm) (WxDxH) | n/a |
| Drawer Size 2 (mm) (WxDxH) | n/a |
| Drawer Material | n/a |
| Number of Baskets | 1 |
| Basket Material | Polythene Coated Wire |
| Basket Size (mm) (WxDxH) | 485mm x 255mm x 171mm |
| | |

Power/Installation

| UK 3 Pin Plug Power Cord | Yes |
|-------------------------------------|------------------|
| EU Schuko 2 pin plug Power Cord | Yes |
| AU Type I Plug Power Cord | No |
| Voltage Supply (V) | 220-240V |
| Frequency (Hz) | |
| Max Power (W) | |
| Max Current Rating (A) | |
| Energy Consumption (kWh/24h) | 0.92kWh/24h |
| Energy Consumption AE (kWh) | 328.5kWh |
| Heat Output Estimated at 22°C (kJ) | 3312kJ |
| Adjustable Feet (Number & position) | 4 All adjustable |

Weights & Dimensions

| Unit External Width (mm) | 595mm |
|-------------------------------------|-----------------------|
| Unit External Depth (mm) | 600mm |
| Unit External Height (mm) | 850mm |
| Unit External Depth Inc Handle (mm) | 660mm |
| Internal Dimensions (mm) (WxDxH) | 495mm x 480mm x 720mm |
| Product Weight (kg) | 39.75kg |
| Packed Width (mm) | 640mm |
| Packed Depth (mm) | 660mm |
| Packed Height (mm) | 910mm |
| Packed Weight (kg) | 44.76kg |
| Country of Origin | China |
| | |

